



ST-NEGATIEF

Negatief T-stuk 90°

Diameters 80 - 800

Rubberen afdichting

Leverbare afmetingen

artikelnummer	naam	d1 (mm)	d3 (mm)	l (mm)	l1 (mm)	l3 (mm)	lp1 (mm)	lp3 (mm)	gewicht (kg)
5050000393	ST 80 100	80	100	160	80	70	40	40	0,49
5050000989	ST 80 125	80	125	185	92,5	75	40	40	0,58
5050000396	ST 100 125	100	125	185	92,5	85	40	40	0,62
5050000899	ST 100 150	100	150	210	105	90	40	40	0,76
5050000397	ST 100 160	100	160	220	110	90	40	40	0,79
5050000900	ST 125 150	125	150	210	105	105,5	40	40	1,05
5050000401	ST 125 160	125	160	220	110	105,5	40	40	1,10
5050000901	ST 125 180	125	180	240	120	105,5	40	40	1,00
5050000402	ST 125 200	125	200	260	130	110,5	40	40	1,15
5050000902	ST 150 160	150	160	220	110	115	40	40	-
5050000903	ST 150 180	150	180	240	120	120	40	40	-
5050000407	ST 150 200	150	200	260	130	120	40	40	1,35
5050000904	ST 160 180	160	180	240	120	125	40	40	1,20
5050000413	ST 160 200	160	200	260	130	125	40	40	1,30
5050000905	ST 160 224	160	224	284	142	130	40	40	-
5050000414	ST 160 250	160	250	310	155	135	40	40	1,60
5050000906	ST 180 200	180	200	260	130	135	40	40	1,55
5050000907	ST 180 224	180	224	284	142	140	40	40	-
5050000908	ST 180 250	180	250	310	155	145	40	40	1,80
5050000909	ST 180 280	180	280	340	170	150	40	40	-
5050000911	ST 200 224	200	224	284	142	150	40	40	1,60
5050000427	ST 200 250	200	250	310	155	155	40	40	2,15
5050000912	ST 200 280	200	280	340	170	160	40	40	-
5050000428	ST 200 315	200	315	375	187,5	165	40	40	2,25
5050000913	ST 224 250	224	250	310	155	165	40	40	1,95
5050000914	ST 224 280	224	280	340	170	170	40	40	-
5050000915	ST 224 315	224	315	375	187,5	175	40	40	-
5050000918	ST 250 280	250	280	340	170	185	40	40	-
5050000443	ST 250 315	250	315	375	187,5	190	40	40	2,95
5050000919	ST 250 355	250	355	415	207,5	200	40	65	3,15
5050000924	ST 280 315	280	315	375	187,5	205	40	40	-
5050000925	ST 280 355	280	355	415	207,5	215	40	65	-
5050000926	ST 280 400	280	400	460	230	220	40	65	-
5050000463	ST 315 355	315	355	415	207,5	230,5	40	65	3,75
5050000464	ST 315 400	315	400	460	230	240,5	40	65	4,05
5050000465	ST 315 450	315	450	510	255	240,5	40	65	4,55
5050000940	ST 355 400	355	400	460	230	260,5	65	65	5,40
5050000473	ST 355 450	355	450	510	255	265,5	65	65	5,70
5050000474	ST 355 500	355	500	560	280	275,5	65	65	6,30

Leverbare afmetingen

artikelnummer	naam	d1 (mm)	d3 (mm)	l (mm)	l1 (mm)	l3 (mm)	lp1 (mm)	lp3 (mm)	gewicht (kg)
5050000483	ST 400 450	400	450	510	255	290	65	65	6,20
5050000484	ST 400 500	400	500	560	280	295	65	65	6,80
5050000952	ST 450 500	450	500	560	280	320	65	65	7,50
5050000490	ST 450 560	450	560	620	310	330	65	65	8,40
5050000491	ST 450 630	450	630	690	345	340	65	65	9,20
5050000498	ST 500 560	500	560	620	310	355	65	65	9,00
5050000499	ST 500 630	500	630	690	345	365	65	65	10,20
5050000959	ST 500 710	500	710	770	385	385	65	100	12,40
5050000505	ST 560 630	560	630	690	345	395	65	65	10,90
5050000968	ST 560 710	560	710	770	385	415	65	100	13,40
5050000969	ST 560 800	560	800	860	430	425	65	100	15,00
5050000980	ST 630 710	630	710	770	385	450	65	100	14,50
5050000508	ST 630 800	630	800	860	430	460	65	100	16,40
5050000988	ST 710 800	710	800	860	430	500	100	100	19,70

Vetgedrukte doorsnedes zijn Eurovent/Luka norm.