



Verloop voor buis (kort geperst)

Diameters 100 - 315

Rubberen afdichting

Leverbare afmetingen

	naam	d1 (mm)	d2 (mm)	l (mm)	lp1 (mm)	lp2 (mm)	gewicht (kg)
	SDNK 100 80	100	80	19	35	35	0.14
	SDNK 125 80	125	80	33	35	35	0.17
	SDNK 125 100	125	100	23	35	35	0.16
	SDNK 150 100	150	100	46	35	35	0.20
	SDNK 150 125	150	125	30	35	35	0.19
	SDNK 160 80	160	80	64	35	35	0.24
	SDNK 160 100	160	100	41	35	35	0.23
	SDNK 160 125	160	125	35	35	35	0.22
	SDNK 160 150	160	150	13	35	35	0.19
	SDNK 180 100	180	100	61	35	35	0.28
	SDNK 180 125	180	125	47	35	35	0.27
	SDNK 180 150	180	150	37	35	35	0.24
	SDNK 180 160	180	160	21	35	35	0.23
	SDNK 200 100	200	100	58	35	35	0.33
	SDNK 200 125	200	125	48	35	35	0.32
	SDNK 200 150	200	150	36	35	35	0.27
	SDNK 200 160	200	160	34	35	35	0.29
	SDNK 200 180	200	180	32	35	35	0.29
	SDNK 224 160	224	160	54	35	35	0.39
	SDNK 224 200	224	200	26	45	35	0.48
	SDNK 250 125	250	125	70	45	36	0.51
	SDNK 250 150	250	150	69	45	35	0.50
	SDNK 250 160	250	160	59	45	35	0.50
	SDNK 250 200	250	200	46	35	35	0.44
	SDNK 250 224	250	224	27	45	45	0.55
	SDNK 315 160	315	160	85	45	36	0.70
	SDNK 315 200	315	200	78	45	35	0.69
	SDNK 315 250	315	250	46	45	45	0.70

Vetgedrukte doorsnedes zijn Eurovent/Luka norm.