

LG Standaard Wifi Pro 3,5/5,0 kW



Wandmodel set type Standaard Wifi Pro R32 single split systeem



Specificaties

SINGLE SPLIT				3,5kW	5,0kW
Capaciteit	Koelen	Min/Nom/Max	W	890/3500/4040	900/5000/5500
	Verwarmen	Min/Nom/Max	W	890/3710/5100	900/5400/6400
Verbruik	Koelen		W	1016	1563
	Verwarmen		W	917	1375
Vermogen	Koelen		W	3,3	5,0
	Verwarmen		W	2,4	4,1
Rendement	EER			3,24	3,23
	SEER			6,6	7,0
	COP			3,91	3,71
	SCOP (gematigd klimaat)			4,0	4,3
Energieklasse	Gematigd klimaat	Koelen/verwarmen	A+	A++	A++
	Warm klimaat	Koelen/verwarmen	A+	A+ / A+++	A+ / A+++
BINNEN				WZ12AWN	WZ18AWN
Geluidsdruk	Koelen	SH/H/M/L/SL	dB(A)	45/41/35/27/19	47/44/39/34/31
	Verwarmen	SH/H/M/L	dB(A)	45/41/35/27	48/44/39/34
Afmetingen		BxHxD	mm	837x308x189	998x345x210
Gewicht			kg	8,3	10,6
Wifi			ja/nee	Ja	Ja
BUITEN				WZ12AWU	WZ18AWU
Geluidsdruk	Koelen		dB(A)	55	53
	Verwarmen		dB(A)	54	55
Luchtstroom			m³/min	27,0	35,0
Afmetingen		BxHxD	mm	717x230x495	770x545x288
Gewicht			kg	23,2	32
Werkingsbreik	Koelen	Min/Max	°C DB	-21~48	-10~48
	Verwarmen	Min/Max	°C DB	-15~24	-15~24
Koelmiddel (R32)	Voorvulling koelmiddel		kg	0,53	0,78
	Extra koelmiddel		g/m	15	16
	T-CO²			0,358	0,527
Koelaansluitingen	Vloeistof		mm/inch	ø 6,35 (1/4")	ø 6,35 (1/4")
	Gas		mm/inch	ø 9,52 (3/8")	ø 12,7 (3/8")
Lengtes	Min/Max		m	3/7,5/15	3/7,5/20
	Voorgevuld		m	7,5	7,5
	Hoogteverschil		m	7	10